

BOARD OF
**BUILDING AND SAFETY
COMMISSIONERS**

MARSHA L. BROWN
PRESIDENT

VAN AMBATIELOS
VICE-PRESIDENT

VICTOR H. CUEVAS
HELENA JUBANY
ELENORE A. WILLIAMS

CITY OF LOS ANGELES

CALIFORNIA



ANTONIO R. VILLARAIGOSA
MAYOR

DEPARTMENT OF
BUILDING AND SAFETY
201 NORTH FIGUEROA STREET
LOS ANGELES, CA 90012

ROBERT R. "BUD" OVROM
GENERAL MANAGER

RAYMOND S. CHAN, P.E., S.E.
EXECUTIVE OFFICER

Tremco, Incorporated
3735 Green Road
Beachwood, OH 44122

Attn: Tim Mattox
(216) 514-7566

Local Representative:
Gus Pinon
(562) 795-7727

RESEARCH REPORT: RR 25299
(CSI #07140)

Expires: May 01, 2012
Issued Date: May 01, 2010
Code: 2008 LABC

GENERAL APPROVAL – Renewal - Tremproof 6100 Membrane for below grade waterproofing

DETAILS

Tremproof 6100 Membrane is hot applied rubberized asphalt specially formulated from asphalts, rubber and inert fillers. The minimum thickness of the installed products is 180 mil.

The approval is subject to the following conditions:

1. Installation of the product shall be in accordance with the manufacturer's instructions and the requirements herein. A copy of this report and the installation instructions shall be provided at each job site by the manufacturer.
2. The product shall be used in well ventilated area.
3. Adjoining sheet edges shall overlap a minimum of 3".
4. All concrete surfaces shall be primed with Tremco Hot Rubber Primer at a rate of 300 to 500 square feet per gallon.

RR 25299
Page 1 of 2

Tremco, Incorporated
RE: Tremproof 6100 Membrane for below grade waterproofing

5. During construction, the membrane shall be covered by a dark color protective barrier where it is exposed to sunlight.

DISCUSSION

The report is in compliance with 2008 Los Angeles Building Code.

The approval is based on technical data and specifications submitted by the manufacturer and test data by a Los Angeles City approved testing agency.

The product can withstand hydrostatic pressure of 30 psi.

Addressee to whom this Research Report is issued is responsible for providing copies of it, complete with any attachments indicated, to architects, engineers and builders using items approved herein in design or construction which must be approved by Department of Building and Safety Engineers and Inspectors.

This general approval of an equivalent alternate to the Code is only valid where an engineer and/or inspector of this Department has determined that all conditions of this Approval have been met in the project in which it is to be used.

WILLIAM STUTSMAN, Chief
Engineering Research Section
201 N. Figueroa St., Room 880
Los Angeles, CA 90012
Phone - 213-202-9812
Fax - 213-202-9942

TV: tvo
RR25299/MSWord2003
R05/01/10
2H6/1402