

BOARD OF  
**BUILDING AND SAFETY**  
COMMISSIONERS

VAN AMBATIELOS  
PRESIDENT

E. FELICIA BRANNON  
VICE PRESIDENT

JOSELYN GEAGA-ROSENTHAL  
GEORGE HOVAGUIMIAN  
JAVIER NUNEZ

**CITY OF LOS ANGELES**  
CALIFORNIA



ERIC GARCETTI  
MAYOR

DEPARTMENT OF  
**BUILDING AND SAFETY**  
201 NORTH FIGUEROA STREET  
LOS ANGELES, CA 90012

FRANK M. BUSH  
GENERAL MANAGER  
SUPERINTENDENT OF BUILDING

OSAMA YOUNAN, P.E.  
EXECUTIVE OFFICER

Elco Construction Products  
701 East Joppa Road  
Towson, Maryland 21286

Attn: Bob Antoinette  
(800) 524-3244

RESEARCH REPORT: RR 25886  
(CSI #05 05 23)

Expires: October 1, 2020

Issued Date: October 1, 2018

Code: 2017 LABC

**GENERAL APPROVAL** – Renewal and Clerical Modification - Elco Bi-Flex and Hilti Bi-Metal Kwik-Flex Structural Fasteners for cold-formed steel, structural steel and aluminum.

## DETAILS

Elco Bi-Flex and Hilti Bi-Metal Kwik-Flex Structural Fasteners are approved to resist tension and shear loads in cold-formed steel, structural steel and aluminum metal-to-metal connections, as tabulated in Attachment. The fasteners are manufactured to ASTM F593 Standard Specification for Stainless Steel Bolts, Hex Cap Screws, and Studs, using series 300 stainless steel alloys, furnished in the cold-worked condition.

Elco Bi-Flex and Hilti Bi-Metal Kwik-Flex Structural Fasteners are identical in design and manufacture except for the product name identification.

Self-drilling fasteners are installed without pre-drilling holes in the receiving member of the connection. The drilling function of the fastener must be completed prior to the lead threads of the fastener engaging the metal. This is accomplished by the fastener pre-drilling a clearance hole in the component being connected to the receiving member. Fasteners must be installed perpendicular to the work surface with a 1,800 to 2,500 rpm screw gun incorporating a depth-sensitive or torque-limiting nose piece. Installed fasteners must protrude through the connected members, with the high-hardness drill point and lead threads extending beyond the connected members.

**The approval is subject to the following conditions:**

RR 25886  
Page 1 of 3

Elco Construction Products

RE: Elco Drill-Flex and Hilti Kwik-Flex Structural Fasteners for Cold-Formed Steel and Aluminum.

1. Steel members shall have a minimum ultimate tensile strength of 58 ksi. Cold-formed steel shall have a minimum yield strength of 60ksi and ultimate strength of 75ksi.
2. The applied tension and shear service (allowable strength design) loads shall not exceed the allowable nominal tension and shear strengths for fasteners as tabulated in Table 1 and Table 2 as shown on the attached sheet.
3. The minimum spacing and edge distance for fasteners shall comply with Table 3 shown on the attached sheet. For steel connections, the minimum spacing distance is three times the diameter of the screw, and the minimum edge distance is 1.5 times the diameter of the screws. For aluminum connections, the minimum spacing distance is four times the nominal diameter of the screw, and the minimum edge distance is two times the nominal diameter of the screws.
4. Calculations demonstrating the applied loads are less than the allowable loads prepared by a California licensed civil or structural engineer or architect must be submitted to the structural plan check section.
5. The allowable loads shall not be increased for wind or seismic forces.
6. Calculations shall be in accordance with the Cold Formed Steel Design Manual, AISI S100-2007. Engineer shall consider all loading conditions acting on connection assembly. Comply with Section 4.5 of the AISI S100-2007 for screws subject to combined shear and pull-over.
7. The nominal strength values contained in this report are not approved for the design of structural diaphragms used to resist wind, seismic and other in-plane lateral loads.
8. Fasteners are to be installed in accordance with the manufacturer's published installation instructions and this report.
9. The screws are identified with a raised circle around a "flag" logo on top of the fastener head.
10. The screws are identified with a number "3" above a flag logo on the top of the fastener head.

**DISCUSSION**

Elco Construction Products

RE: Elco Drill-Flex and Hilti Kwik-Flex Structural Fasteners for Cold-Formed Steel and Aluminum.

The clerical modification is to change the address of the petitioning organization and update the report to the 2017 Los Angeles City Building Code.

The report is in compliance with the 2017 Los Angeles City Building Code.

The approval is based on tests and calculations.

Addressee to whom this Research Report is issued is responsible for providing copies of it, complete with any attachments indicated, to architects, engineers and builders using items approved herein in design or construction which must be approved by Department of Building and Safety Engineers and Inspectors.

This general approval of an equivalent alternate to the Code is only valid where an engineer and/or inspector of this Department has determined that all conditions of this approval have been met in the project in which it is to be used.

---

QUAN NGHIEM, Chief  
Engineering Research Section  
201 N. Figueroa St, Room 880  
Los Angeles, CA 90012  
Phone - 213-202-9812  
Fax - 213-202-9943

QN  
RR25886  
R10/15/2018  
TLB1800252  
2209.1

Attachment: 1-page: Tables of Allowable Tension and Shear Service Loads and Minimum Spacing and Edge Distance.