

CITY OF LOS ANGELES

CALIFORNIA



ERIC GARCETTI
MAYOR

BOARD OF
**BUILDING AND SAFETY
COMMISSIONERS**

VAN AMBATIELOS
PRESIDENT

E. FELICIA BRANNON
VICE PRESIDENT

JOSELYN GEAGA-ROSENTHAL
GEORGE HOVAGUIMIAN
JAVIER NUNEZ

DEPARTMENT OF
BUILDING AND SAFETY
201 NORTH FIGUEROA STREET
LOS ANGELES, CA 90012

FRANK M. BUSH
GENERAL MANAGER
SUPERINTENDENT OF BUILDING

OSAMA YOUNAN, P.E.
EXECUTIVE OFFICER

Guardian Pool Fence Systems, Inc
14715 Aetna St.
Van Nuys, CA 91411

Attn: Steven Sadinsky
(818) 767-7233

RESEARCH REPORT: RR 25900
(CSI # 07110)

Expires: April 1, 2020
Issued Date: April 1, 2018
Code: 2017 LABC

GENERAL APPROVAL – Renewal and Clerical Modification - Guardian Pool Fence System with Permanent Mounting.

DETAILS:

The Guardian Pool Fence System for use as a safety barrier for swimming pools is a fixed 5 feet tall fencing system using a polyester mesh material. The system is fixed by securing the fence poles spaced a maximum of 30" o.c. for the Original Pool Fence, 30" or 36" o.c. for the Premier Pool Fencing.

The Original Pool Fencing utilizes poles which are constructed of T6 marine grade aluminum that are internally reinforced with a tri-core design. The poles are inserted into a High Density Polyethylene (HDPE) and/or nylon & glass locking sleeve anchored to the aluminum poles with two stainless steel screws. The locking sleeve is installed into the deck using a 1-1/4-inch diameter hole and a minimum 4" inch embedment using an adhesive as recommended by Guardian Pool Fence Systems, Inc.

The Premier Pool Fencing System utilizes poles which are constructed with T6 marine grade aluminum which incorporates a 1/2-inch diameter schedule 80 PVC reducer bushing and 1/2-inch diameter 304 stainless steel pin. The stainless steel pin is inserted into a High Density Polyethylene (HDPE) and/or nylon & glass locking sleeve anchored to the pole with two stainless steel screws. The Sleeve is installed into the deck using a 5/8-inch diameter hole and a minimum 4" inch embedment, using an adhesive as recommended by Guardian Pool Fence Systems, Inc.

Access to the pool area is through a Guardian Pool Fence System Self Closing, Self latching, key-locking patented gate. The gate uses a Magna Latch magnetically operated latch and is key lockable. An internal ABS adapter at the bottom of the gate allows for the 1/2-inch 304 stainless steel rods to protrude 4-inches from the bottom of the aluminum gate. The stainless steel rods are then inserted into the locking sleeves. The gate is fixed using the same locking sleeve that is used

Guardian Pool Fence Systems, Inc
RE: Guardian Pool Fence System with Permanent Mounting.

on the fence.

The approval is subject to the following conditions:

1. Fencing shall only be used with permanent mounting device as shown on the attached detail.
2. Fencing shall be permanently installed and shall not be moved. Moveable fencing used to meet the private swimming pool barrier requirements is not allowed as it is a violation of permanent barrier requirements specified in section 91.3109.4.1 of the Los Angeles City Municipal Code.

DISCUSSION

The clerical modification is to update the report to the 2017 Los Angeles City Building Code.

The report is in conformance with the 2017 Los Angeles City Building Code.

To unlatch the gate a lift knob located at the top most of the gate has to be lifted to release the magna latch.

Approval is based on testing in accordance with ASTM F 2286 and by demonstrating that the pool enclosure can be installed in a permanent manner.

This general approval of an equivalent alternate to the Code is only valid where an engineer and/or inspector of this Department has determined that all conditions of this Approval have been met in the project in which it is to be used.

Addressee to whom this Research Report is issued is responsible for providing copies of it, complete with any attachments indicated, to architects, engineers and builders using items approved herein in design or construction which must be approved by Department of Building and Safety Engineers and Inspect

QUAN NGHIEM, Chief
Engineering Research Section
201 N. Figueroa St., Room 880
Los Angeles, CA 90012
Phone- 213-202-9812
Fax- 213-202-9943

QN
RR25900/MSWord2013
R04/15/18
TLB1800093
3109.4

Attachment: Permanent Connection Detail (1-Page)